



The KX-5205 features a 15 inch bass driver and an extended response 1 ¾ inch diameter voice coil compression driver, coupled with Krix proprietary 90° x 40° horn. Using sophisticated loudspeaker modelling techniques, the acoustic loading and pattern control have been engineered to achieve industry leading low distortion and smooth directivity characteristics.

Building on a long and successful history within the cinema industry, our in-house research, development and manufacturing team deliver a strong focus on quality and rigorous production standards. Every speaker that leaves Krix has been fully tested in an advanced acoustic measurement chamber. Tight production tolerances are upheld to ensure best-in-class product quality and reliability.

FEATURES

- Extended response 35mm voice coil compression driver for improved dialogue fidelity.
- Patented Constant Directivity Horn technology for precision coverage, extremely uniform frequency response. The result is that every seat in the cinema experiences improvements in clarity and definition.
- Krix proprietary 'X Bracing' system within the low frequency enclosure for standing wave suppression and reduced panel resonance.
- Krix engineered bass driver featuring, large ferrite magnet structure, dual aluminium shorting rings and symmetrical gap geometry for minimum distortion at all levels.



System options	Mono-amplified (passive crossover)	Bi-amplified	
Product code	KX-5205.M	KX-5205.B	
Frequency		Low	High
Sensitivity (2.83 V/m, Half space ³)	97 dB	97 dB	110 dB
Input power rating ²	450 W	310 W	45 W
Impedance	8 Ω	4 Ω	8 Ω
Crossover frequency	1600 Hz (Low - High)	1600 Hz (Low - High)	
Frequency range	32 – 19,000 Hz (-6 dB)		
Nominal dispersion	90° Horizontal, 40° Vertical		
Dimensions	1140 (H) x 565 (W) x 460 (D) mm	45 (H) x 22 ¼ (W) x 18 (D) inches	
Net weight	44 kg	97 lbs	

DETAILED SPECIFICATIONS

	Mono-amplified (passive crossover)	Low frequency	Horn system
Part Number ⁵	KX-5205.M	KX-2010	KX-3420
Sensitivity			
1 W/m, Free space	96 dB ¹	96 dB	110 dB
1 W/m, Half space ³	98 dB ¹	98 dB	110 dB
2.83 V/m, Free space	95 dB	95 dB	110 dB
2.83 V/m, Half space ³	97 dB	97 dB	110 dB
Impedance			
Nominal	8 Ω	8 Ω	8 Ω
Minimum	8.1 Ω	8.0 Ω	7.2 Ω
Maximum Input Voltage ⁴	60 V	50 V	19 V
Maximum Input Power			
Continuous ²	450 W	310 W	45 W
Peak	1800 W	1240 W	180 W
Recommended Processing	Subsonic 30 Hz, >12 dB/oct	Subsonic 30 Hz, >12 dB/oct	Contact Krix for details
Low frequency transducer	1 x 380 mm (15 inch) paper cone driver, ferrite magnet, vented pole piece, 75 mm (3 inch) edge wound copper voice coil, dual aluminium shorting rings.		
Low frequency enclosure	Vented B4 alignment tuned to 36 Hz, Krix proprietary 'X bracing', optimally damped with polyester fibre, MDF black vinyl finish.		
High frequency transducer	1 x 35mm (1.4 inch) compression driver, ferrite magnet, coated titanium diaphragm, polyimide surround.		
Horn	90° x 40° constant directivity, thermoset resin reinforced with glass fibre.		
Horn bracket	Tilt 0° to 15° downwards: Swivel ±15° degrees.		
Terminals	Krix proprietary, high current binding posts featuring an 8mm hole to accept large diameter cable. High visibility polarity indicators.		

NOTES

- All measurements and specifications are made in accordance with AES2-2012 and in a form compatible with Dolby® Atmos™ calculator.
 - Due to continued development, specifications may change without notice.
 - Manufactured and sold under US Patents 7,044,265 B2 and 2011/0153282 A1.
1. Sensitivity measurements adjusted to the nominal 1W input power, calculated from the real part of the electrical input impedance over the operating frequency range.
 2. Maximum AES continuous power capacity (AES2-2012) band limited test signal duration of two hours.
 3. Half space sensitivity based on partial increase due to rear wall loading at low frequencies estimated from the directivity index over operating frequency range.
 4. RMS voltage required to deliver the maximum continuous power to the loudspeaker, IEC shaped pink noise with duration of two hours.
 5. The KX-5205 is shipped in two parts comprising of a KX-2010 (Low Frequency component) and KX-3420 (Horn system component).

KX-5205

2-WAY SCREEN CINEMA SYSTEM

DETAILED DIMENSIONS



